MasterGrid Shadowline Wall Angle Technical Datasheet: June 2025

Siniat MasterGrid Shadowline Wall Angle

Description

Siniat MasterGrid Shadowline wall angle is a roll formed light gauge steel section designed to be used in a exposed grid suspended ceiling application to provide a neat 20mm shadow edge along the junction between ceiling and wall.

Intended use

All Internal commercial and residential exposed grid suspended ceiling applications.

Compliance to Standards

SANS 2001:EC1:2010: South African National Standard: Construction Works: Part EC1: Ceilings, partitions and access flooring. EN 13964: 2004, Amended 2006: European Norm: Suspended Ceilings: Requirements and Test Methods

Product Tolerances

Dimension	Unit	Tolerance
Leg sizes	13x20x20x24mm Overall 33x44mm	± 0.5mm
Flatness	0mm	± 1.5mm
Twist	± 0°	≤2°
Length	3600mm	± 5.00mm

Product Physical Properties

Property	Unit	Typical Value
Base Material	White Chromadek	0.5mm
Corrosion resistance All indoor Areas	Class	C1

General storage, handling and installation instructions

Storage	Store in dry, flat conditions. Ensure safe stacking up to maximum 2 pallets.
Handling	Use suitable handling equipment to avoid damage when lifting.

Please consult our website. www.siniat.co.za if further information is required.



Etex South Africa, 2 Setchell Road, Roodekop, Gauteng, South Africa.

Tel: +27(0) 11 389 4500 | Email: contactus.siniat@etexgroup.com | www.siniat.co.za

Directors: S Carter (British), J L G Bernard (French)