

Technical Datasheet: Oct 2025

Siniat Drywall CornerBead

Description

Siniat Drywall Corner Beads are perforated and roll formed light gauge steel sections designed to be used in a multitude of applications to provide straight and accurate corners with added strength in all drywall systems including walls, bulkheads, complex plastered ceilings and flush plastered ceilings.

Intended use

All Internal commercial and residential drywalling and ceiling applications.

Compliance to Standards

SANS 2001:EC1:2010: South African National Standard: Construction Works: Part EC1: Ceilings, partitions and access flooring. EN 13964: 2004, Amended 2006: European Norm: Suspended Ceilings: Requirements and Test Methods

Product Tolerances

Dimension	Unit	Tolerance
Leg widths	28 x 28mm	± 0.5mm
Flatness	0mm	± 1.5mm
Twist	± 0°	≤2°
Length	2700/3000/3600mm	± 5.00mm

Product Physical Properties

Property	Unit	Typical Value
Base Material	Galvanised Steel 0 mm	0.40mm
Corrosion resistance All indoor Areas	Class	C1

General storage, handling and installation instructions

Storage	Store in dry, flat conditions. Ensure safe stacking of bundles.
Handling	Use suitable handling equipment to avoid damage when lifting.

Please consult our website. www.siniat.co.za if further information is required.



Etex South Africa, 2 Setchell Road, Roodekop, Gauteng, South Africa. Tel: +27(0) 11 389 4500 | Email: contactus.siniat@etexgroup.com | www.siniat.co.za

Directors: R Roach, J L G Bernard (French)