

# Siniat EasyLite plaster

# **Description**

**Siniat EasyLite** is a gypsum plaster-based product designed to level uneven internal surfaces and to smooth levelled surfaces for a superior and smooth finished result. It is a lightweight all-in-one lightweight plaster.

#### Intended use

Application onto the following surfaces:

- Plasterboard
- Sand and cement plastered walls
- Concrete slabs and soffit
- Brick surfaces

# **Physical properties:**

Appearance:	Fine white powder with particles, odourless		
Packaging:	Siniat EasyLite multipurpose (blue bag) 20kg and 40kg Bags		
	Siniat EasyLite Skimming for Coastal (yellow bag) 40kg		
Water Plaster Ratio:	2:1 (one water, 2 parts plasters)		
Mixing:	Do not mix more than what can bee used in 1 hour		
Composition:	Calcium Sulphate Hemihydrate, silica's, accelerant, and retarder		
Combustibility:	Non-Combustible		
Approximate PH:	> 9		
Application Temperature:	Between 5°C and 40°C		
Shelf Life:	9 Months – keep dry and covered		

## Coverage:

EASILY DETERMINE THE M <sup>2</sup> COVERAGE PER 20KG/40KG BAGS										
Thickness in mm	3	4	5	6	7	8	9	10		
20KG bag m² coverage	12	10	8	6,5	5,5	5	4,5	4		
40KG bag m² coverage	24	20	16	13	11	10	9	8		



Etex South Africa, 2 Setchell Road, Roodekop, Gauteng, South Africa.

Tel: +27(0) 11 389 4500 | Email: contactus.siniat@etexgroup.com | www.siniat.co.za

Directors: S Carter (British), J L G Bernard (French)





#### **Caution**

**Siniat EasyLite** should not be applied in areas where high moisture levels occur, such as bathrooms and laundries.

Please note the following:

- Siniat EasyLite is for internal use only
  - Siniat multipurpose (blue bag) is used in interior part of the country
  - o Siniat Skimming plaster (yellow bag) for coastal is used in the coastal regions
- It is not made for human consumption
- Keep out of reach of children
- Keep your workplace ventilated
- Use PPE for protection

#### Finishing suggestion

**Siniat EasyLite** (blue bag) is finished off with a rubber float to bring out the excess EasyLite and to smoothen it.

**Siniat EasyLite** plaster needs to be primed before applying paint, please consult your painting supplier for a suitable plaster primer.

Variance from the application instructions will result in dust or residue on the surface after set and dry time is completed, applying a primer will assist against potential delamination of finishing materials, due to deviance from the application and cleaning instructions. It is important that you adhere to the application instructions as stipulated.

#### **Benefits:**

- Easy to mix.
- Quick and easy to apply
- Wide application range
- Skimmed surfaces are highly resistant to impact and scratches.
- Skimmed surfaces can be painted directly after the product is set and dry.
- No sanding required.

## Storage:

• Store **Siniat EasyLite** inside, on a level surface, off the floor, in a dry place protected from the weather.



**Etex South Africa**, 2 Setchell Road, Roodekop, Gauteng, South Africa. **Tel:** +27(0) 11 389 4500 | **Email:** contactus.siniat@etexgroup.com | www.siniat.co.za

**Directors:** S Carter (British), J L G Bernard (French)





- Moisture is to be avoided. Open bags that still contain product are to be sealed tightly to avoid dust spreading and to protect the product.
- Care should be taken when lifting single bags of plaster by hand to ensure that back injuries do not occur. Pallets of plaster to be moved by mechanical handling equipment only.

## **EasyLite Tool requirements:**

- Flexible container for mixing
- Hand mixer or machine mixer
- Hand hawk
- Rubber float (if needed)
- Steel trowel
- Block brush
- PPF

### **Health & Safety**

Please read the Plasters Health and Safety Datasheet available on our website. www.siniat.co.za



